

NWS-CE1 X4

TASSELLO PASSANTE AD ESPANSIONE

Con Dado e Rondella

THROUGHBOLT

With Nut and Washer

GOUJONS

Avec Écrou et Rondelle

ANKER

Mit Mutter und Scheibe



CODICE CODE CODE NUMMER	ARTICOLO ITEM TYPE ARTIKEL		LUNGH. TOT. TOTAL LENGTH LONGUEUR TOT. LÄNGE		SPESSORE FISSABILE MAX. FIXTURE THICKNESS MAX. ÉPAISSEUR FIXABLE MAX. BEFESTIGUNGSDICKE	
			L [mm]		t _{fix} [mm]	Nr.
710600	NWS-CE1 X4 8-10-21/75	M8	75	C1 C2	10-21**	100
710601	NWS-CE1 X4 8-15-26/80 ⚠	M8	80	C1 C2	15-26**	100
710602	NWS-CE1 X4 8-30-41/95 ⚠	M8	95	C1 C2	30-41**	100
710603	NWS-CE1 X4 8-50-61/115 ⚠	M8	115	C1 C2	50-61**	100
710604	NWS-CE1 X4 8-100-111/165 ⚠	M8	165	C1 C2	100-111**	50
710605	NWS-CE1 X4 10-10-30/90	M10	90	C1 C2	10-30**	50
710606	NWS-CE1 X4 10-15-35/95 ⚠	M10	95	C1 C2	15-35**	50
710607	NWS-CE1 X4 10-20-40/100 ⚠	M10	100	C1 C2	20-40**	50
710608	NWS-CE1 X4 10-30-50/110 ⚠	M10	110	C1 C2	30-50**	50
710609	NWS-CE1 X4 10-50-70/130 ⚠	M10	130	C1 C2	50-70**	50
710610	NWS-CE1 X4 10-75-95/155 ⚠	M10	155	C1 C2	75-95**	50
710611	NWS-CE1 X4 10-100-120/180 ⚠	M10	180	C1 C2	100-120**	50
710612	NWS-CE1 X4 10-150/230 ⚠	M10	230		150	25
710613	NWS-CE1 X4 12-10-30/105 ⚠	M12	105	C1 C2	10-30**	25
710614	NWS-CE1 X4 12-15-35/110 ⚠	M12	110	C1 C2	15-35**	25
710615	NWS-CE1 X4 12-20-40/115	M12	115	C1 C2	20-40**	25
710616	NWS-CE1 X4 12-30-50/125 ⚠	M12	125	C1 C2	30-50**	25
710617	NWS-CE1 X4 12-50-70/145 ⚠	M12	145	C1 C2	50-70**	25
710618	NWS-CE1 X4 12-65-85/160 ⚠	M12	160	C1 C2	65-85**	25
710619	NWS-CE1 X4 12-85-105/180 ⚠	M12	180	C1 C2	85-105**	25
710620	NWS-CE1 X4 12-105-125/200 ⚠	M12	200	C1 C2	105-125**	25
710621	NWS-CE1 X4 12-125/220 ⚠	M12	220		125	25
710622	NWS-CE1 X4 12-160/255 ⚠	M12	255		160	20
710623	NWS-CE1 X4 12-190/285 ⚠	M12	285		190	20
710624	NWS-CE1 X4 12-230/325 ⚠	M12	325		230	20
710625	NWS-CE1 X4 16-5-25/125 ⚠	M16	125	C1 C2	5-25**	20
710626	NWS-CE1 X4 16-15-35/135 ⚠	M16	135	C1 C2	15-35**	20
710627	NWS-CE1 X4 16-25-45/145	M16	145	C1 C2	25-45**	20
710628	NWS-CE1 X4 16-50-70/170 ⚠	M16	170	C1 C2	50-70**	20
710629	NWS-CE1 X4 16-80-100/200 ⚠	M16	200	C1 C2	80-100**	10
710630	NWS-CE1 X4 16-100/220 ⚠	M16	220		100	10
710631	NWS-CE1 X4 16-160/280 ⚠	M16	280		160	10
710632	NWS-CE1 X4 20-30/165	M20	165		30	10
710633	NWS-CE1 X4 20-60/195 ⚠	M20	195		60	10
710634	NWS-CE1 X4 20-100/235 ⚠	M20	235		100	5
710635	NWS-CE1 X4 20-130/265 ⚠	M20	265		130	5
710636	NWS-CE1 X4 20-150/285 ⚠	M20	285		150	5
710637	NWS-CE1 X4 24-30/200 ⚠	M24	200	C1 C2	30	10
710638	NWS-CE1 X4 24-60/230 ⚠	M24	230	C1 C2	60	5
710639	NWS-CE1 X4 24-75/245 ⚠	M24	245		75	5

⚠ Su richiesta > On demand > Sur demande > Auf Wunsch

(**) Affondamento ridotto
Reduced embedment depth
Profondeur d'ancrage réduite
Reduzierter Verankerungstiefe